



**+ DIS-CCU**  
 Central control unit for use with MXC-series, 5900-series or 6000-series conference and discussion units.

DCS-LAN CABLE



**+ MXC620-F**  
 Chairman or Delegate flush mount conference unit  
 NFC card slot, channel selector, PTT and 3.5mm Headphone Jack.

DCS-LAN CABLE



**+ MXC630-F**  
 Chairman or Delegate flush mount conference unit with NFC card slot, channel selector, PTT, 3.5mm headphone jack and 5 backlit voting buttons.

DCS-LAN CABLE



**+ MXC615**  
 Chairman, Delegate or Dual Delegate modes with two channel selectors, each with 3.5mm headphone jack and optional Braille overlay.

DCS-LAN CABLE



**+ MXC620**  
 Chairman, Delegate or Dual Delegate modes with two channel selectors, each with 3.5mm headphone jack, NFC card slot and optional Braille overlay.

DCS-LAN CABLE



**+ MXC630**  
 Configurable as Delegate or Chairman, with 5 voting buttons, participant identification via NFC card and a single channel selector with OLED display. Two 3.5mm headphone jacks and integrated Braille labels on speak and function buttons.

DCS-LAN CABLE



**+ MXC640**  
 Chairman, Delegate or Dual Delegate modes with a 4.3" or 110mm capacitive touchscreen display to vote, view agenda or speaker information etc. Two channel selectors, each with 3.5mm headphone jack and participant identification using NFC card. Integrated Braille labels on speak and function buttons.

DCS-LAN CABLE



**+ MXCSIGN**  
 Dual sided "Name Sign" with E-Paper technology providing high contrast for maximum readability and wide viewing angle. High resolution 1900 x 460 pixels, black/white, 4 bit greyscale and connected via DCS-LAN. Programmable via SW 6000 or CCU/USB when used in standalone mode. Can display name for one or two participants, retains image when disconnected, can be top-mounted or flush-mounted to table.

DCS-LAN CABLE

DCS-LAN CABLE



### + MXCIC

Portable Interpretation Console, which meets ISO 20109. Large color display showing relay and outgoing language channels along with speak/request list. Eight relay buttons and three outgoing languages with two 3.5mm TRRS headset jacks which are compatible with IH6500 headset. One 3.5mm TRS headphone jack along with an integrated loudspeaker and NFC card reader. Integral Braille labels and audible cues for visually impaired users.

3.5 MM TRRS  
HEADSET  
JACK



### + IH6500

Interpreter Headset

DCS-LAN CABLE



### + MXCMIU

Modular Interface Unit, accommodates 1 or 2 faceplate units.

HDMI



### + MXCMIU-FL

Chairman or delegate includes speaker.

DCS-LAN CABLE



### + MXCMIU-FS

Chairman or delegate no speaker.

HDMI



### + MXC-ACC-RIB

Redundancy Interface Box which allows redundant loop cabling and diagnostics for enhanced system reliability.

DCS-LAN CABLE

+



### + MXC416/C

16" Cardioid Microphone  
(interchangeable head) 40 cm

### + MXC420/C

20" Cardioid Microphone  
(interchangeable head) 50 cm

### + MXC416DF/C

16" Dual Flex Microphone  
(interchangeable head) 40 cm

### + MXC420DF/C

20" Dual Flex Microphone  
(interchangeable head) 50 cm

### + MXC406/MS

6" Shotgun Microphone for MXC 15 cm


### + MXCDUALCARD-10PK

Chip + NFC card for DIS, MXC & MXCW use. Configurable with a 3rd-party NFC card writer & Shure NFC Programmer Application.



### + MXCNFCCARD-10PK

NFC card for MXC & MXCW use. Configurable with a 3rd-party NFC card writer & Shure NFC Programmer Application.



### + REPLACEMENT BUTTONS

MXC615/620-ACC-CM

3 Chairman buttons, All Delegates Off, Mute All, Next On

MXC630/640-ACC-CM

3 Chairman buttons, All Delegates Off, Mute All, Next On

MXC615/620-ACC-A/B

A & B buttons for dual delegate function, 10 each

MXC630/640-ACC-A/B

A & B buttons for dual delegate function, 10 each

MXC615/620-ACC-RPY

10 Reply buttons

MXC630/640-ACC-RPY

10 Reply buttons

MXC615/620-ACC-M

10 Mute buttons

MXC630/640-ACC-M

10 Mute buttons

### + CONTACT

SHURE UK

Unit 2, The IO Centre Lea Road  
Waltham Abbey, Essex EN9 1AS  
United Kingdom

Tel.: 01992703058

Email: [ukinfo@shure.com](mailto:ukinfo@shure.com)